

# SMARTDRI HAND DRYERS

## **A290PE Hand Dryer with DTI - *ANTIMICROBIAL* HIGH EFFICIENCY AUTOMATIC - No. HD15363**



ARDRICH HYGIENE PTY LIMITED  
AUSTRALIA  
1 800 058 655  
E [info@ardrich.com.au](mailto:info@ardrich.com.au)

ARDRICH LIMITED  
NEW ZEALAND  
0800 80 2861  
E [info@ardrich.co.nz](mailto:info@ardrich.co.nz)

# A290PE Hand Dryer With DTI - ANTIMICROBIAL HIGH EFFICIENCY AUTOMATIC – No. HD15363



- **FAST DRY TIME**
- **ANTIMICROBIAL INFUSED PLASTICS**
- **DTI - DRY TIME INDICATOR - LED DISPLAYS THE DRYING CYCLE FOR CLEAN DRY SKIN - OPTIMUM HAND HYGIENE**
- **FULLY AUTOMATIC INFRA-RED OPERATION**
- **ENERGY EFFICIENT - VERY LOW OPERATING COST**
- **POWERFUL AIR PERFORMANCE**
- **COMPACT SIZE – SMALL AND POWERFUL**

**Safe Surfaces.** Our revolutionary antimicrobial infused components inhibit the growth of microbes including Staphylococcus and E.coli. Components are manufactured from special resins using EPA approved silver ion technology that infuses plastic parts and coatings with antimicrobial properties.

## SPECIFICATIONS

Construction: All plastics are flame retardant to UL94 VO, Class II double insulated, enclosure splash/drip proof to IPX4, non-corrosive.  
Gross weight 2 kgs. Shipping weight 2.2 kgs.  
Colour: WHITE with grey trim.  
Electrical rating 220-240 V~ 50Hz, 1.71 kW, 7.4 AMP  
Noise level 69 dB. Air volume 5.4 M3/min. Air velocity 175 km/hr.

## SIZE

Height - 220 mm, Width - 210 mm, Depth - 163 mm

## PLANNING

Generally, one hand dryer is recommended for every two hand basins. For heavy use in large washrooms, use two hand dryers for every three basins.

## ELECTRICAL SAFETY APPROVALS

AS3304, AS3300, NZ6362, NZ6300, IEC335-2-23:1996, IEC 335-1:1991 incl Amend 1, EN55014, EN50082-1, EN60555-2/3, International CB Text Certificate No. AU0182, Certificate of suitability No. Q070141

## ELECTRICAL CONNECTION & ADDITIONAL NOTES

This dryer is double insulated and does not require earthing/grounding. Dryers are provided with a supply cord and plug. Installation and servicing should be carried out by a qualified person. Dryer(s) may be fixed wired. Wiring should emerge from the wall at the position marked - Fixed wiring entry.

## RECOMMENDED MOUNTING HEIGHTS

From the floor to the bottom of the dryer:  
Men's washrooms - 1200mm.  
Women's washrooms - 1150mm.  
Children's washrooms - ages up to 10 - 860mm.  
Children's washrooms - ages up to 16 - 1120mm.  
Disabled person's washrooms - 1015mm.

## TOTAL SATISFACTION WARRANTY

Electronic Control Only Warranty – 2 years  
Motor Carbon Brushes Only Warranty – 3 years  
All other components - 10 years

**DISABLED PERSON COMPLIANT**

**EMC COMPLIANT** Z184

